

MOTOR COIL-SHORTING DETECTING UNIT

CROSS-REFERENCE TO RELATED APPLICATION

The present invention is related to Japanese
5 patent application No. 2000-127368, filed April 27, 2000;
the contents of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to a coil short
10 detecting unit, and more particularly, to a coil short
detecting unit that detects the existence of a coil short
in a motor.

BACKGROUND OF THE INVENTION

15 Conventionally, a coil short in a DC motor is
detected by using a sensor magnet, a Hall element, a
controller or the like. Here, the sensor magnet,
magnetized at multiple poles in the direction of rotation,
is provided on a rotation shaft. The Hall element detects
20 the rotation speed of the rotation shaft by detecting
magnetic field changes due to the rotation of the sensor
magnet. The controller determines a coil short by
detecting rotation speed change due to the coil short.
However, positioning the Hall element relative to the
25 sensor magnet is difficult, and attachment requires high
accuracy. Further, two parts, the sensor magnet and the
Hall element, must be mounted, thereby increasing the

Ins. a. conc'd. on the current or voltage varied due to motor rotation, shorting is determined irrespective of motor load.

In another aspect, the determining means determines a short based on ripple variations of the current value or voltage value supplied to the motor from the power source in. Here, the ripple variations are detected through the detecting means. Therefore, a short is determined based on the ripple variations of the current or voltage supplied to the motor from the power source. Here, the ripple variations during normal operation and those during a short are different.

Ins. a. 2. In another aspect, the determining means includes a temperature correction circuit for correcting any pre-stored reference current value or voltage value supplied from the power source during normal operation according to a circumferential temperature. Therefore, the determining means includes the temperature correction circuit for correcting the pre-stored current or voltage reference supplied from the power source during normal operation. According to another aspect, the stop control means stops power supply for the motor when the determining means determines that the coils has shorted.

In another aspect, an abnormality informing means is provided for informing a user of motor abnormality when the coil shorting is determined by the determining means. Therefore, the abnormality informing means informs a user of motor abnormality when it is determined by the determining

Ins.
A2
encd.

~~means that the coils has shorted. A stop control means for stopping power supply for the motor when the coil shorting is determined by the determining means is provided.~~

Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are intended for purposes of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

FIG. 1 is a schematic view for a controller for a motor according to an embodiment of the present invention;

FIG. 2 is a schematic view of a motor according to the present invention;

FIG. 3A is a graph showing current variations during motor rotation for a normal case according to the invention;

FIG. 3B is a graph showing current variations during motor rotation for coil shorting according to the invention;

FIG. 4A is a graph of a current value during motor rotation during normal operation; and

FIG. 4B is a graph of a current value during motor rotation during coil shorting.

DETAILED DESCRIPTION OF THE INVENTION

5 As shown in FIG. 2, a rotor 2 of the motor 1 is provided with coils 3a - 3l forming twelve magnetizing coils and a commutator 4 including twelve commutator segments 4a - 4l. Both ends of each of the coils 3a - 3l are connected to neighboring commutator segments 4a - 4l, respectively. The
10 motor 1 has an anode brush 5a and a cathode brush 5b that slides over the commutator 4 (commutator segments 4a - 4l). Electric power is supplied to the brushes 5a, 5b from a controller 10 as shown in FIG. 1.

The controller 10 has a driving circuit 11, and driving
15 power is supplied to the driving circuit 11 from a power source 12. The driving circuit 11 is provided with first and second terminals. The first terminal is connected to the anode brush 5a through a current sensor 13, and the second terminal is connected to the cathode brush 5b. The
20 current sensor 13 is provided between the driving circuit 11 and the anode brush 5a through a coupling cable. The driving circuit 11 is controlled by the controller 14. That is, the driving circuit 11 supplies driving power to the brushes 5a, 5b based on the control of the controller 14,
25 thereby controlling the rotation speed of the motor 1.

Ins. a3.7
~~Detection signals from the current sensor 13, based on values of current supplied to the motor 1 (anode brush~~

5a) by the driving circuit 11, are input to controller 14. The controller 14 determines whether or not the coils 3a - 31 has shorted based on the input detection signals.

Here, FIG. 3A shows variations (ripple) of the current supplied to the motor 1 when the motor 1 rotates when all of the coils 3a - 31 are normal (the coils 3a - 31 are not shorted). In the same drawing, an average current variation (in the present embodiment, an average variation of a ripple which is a minimum current value out of a max current value per unit rotation) is indicated by "I1". On the other hand, FIG. 3B shows the variations of the current when the motor 1 rotates when at least one of the coils 3a - 31 is shorted. In the same drawing, the average current variation is indicated by "I2" which is larger than "I1". The reason is that current routes are changed between the original case (normal case) and when coils 3a - 31 are shorted.

In the controller 14, the average current variation "I1" during normal operation is stored as a first reference value. When an average current variation supplied to the motor 1 becomes higher than an upper limit determination value, set slightly higher than the first reference value "I1", based on the detection signals from the current sensor 13, the controller 14 determines that at least one of the coils 3a - 31 is shorted. Here, the controller 14 is provided with a temperature correction circuit 14a. Then, the stored first reference value "I1" is corrected by the

temperature correction circuit 14a according to a circumferential temperature, thereby reducing adverse effects on determination due to circumferential temperature variations.

INS
a4

10 ~~When the average current variation supplied to the~~
motor 1 becomes less than a lower limit determination value,
set slightly less than the first reference value "I1", motor
1 is determined to be under a rotation constraint condition
due to its load. FIG. 4A shows a current value during the
motor rotation constraint due to its load in the normal case
(when coils 3a - 31 are not shorted). In the same drawing,
the current value is indicated by "I3". On the other hand,
FIG. 4B shows a current value during the motor rotation
15 constraint due to its load during shorting of the coils 3a -
31. In the same drawing, the current value is indicated by
"I4" which smaller than normal. The reason is also that
current routes are changed between the original case (normal
case) shorting of coils 3a - 31.

20 In the controller, the current value "I3" during a
normal state is stored as a second reference value. When
current variation is lower than the lower limit value and
becomes less than a determination value, set slightly less
than a second reference value "I3", at least one of the
coils 3a - 31 is determined to be shorted. The stored
25 second reference value "I3" is corrected according to a
circumferential temperature by the temperature correction
~~circuit 14a provided in the controller 14, thereby reducing~~

Ins. a4 cancelled.

~~adverse effects for determination due to the circumferential~~
temperature variations. When the controller 14 determines
that the coils 3a - 31 are shorted in this manner, the
controller 14 stops power supply to motor 1 from driving
5 circuit 11, and turns on a warning lamp 15.

(1) The current sensor 13 detects the value of the
current supplied to the motor 1 from the power source, and
the controller 14 determines a short of the coils 3a - 31 by
comparing the detection result from the current sensor 13
10 and the pre-stored current value supplied from the power
~~source.~~

(2) The controller 14 is provided with the temperature
correction circuit 14a for correcting the pre-stored
reference current value supplied from the power source
15 during normal operation according to a circumferential
temperature. Therefore, the adverse effect on determination
due to circumferential temperature variations is reduced by
the temperature correction circuit 14a.

(3) When the controller 14 determines that any one of
20 the coils 3a - 31 has shorted, the controller 14 stops power
supply for the motor 1.

Ins. a6

~~(4) In the present embodiment, the warning lamp 15,~~
which informs a user that the motor 1 is malfunctioning when
the controller 14 determines that the coils 3a - 31 has
25 ~~shorted, is provided.~~

The embodiment of the present invention can be modified
at least in the following manners.

In the above embodiment, the shorting is determined by using an average variation of a value which is a minimum value out of a maximum value per unit rotation. However, without limitation to this manner, shorting can be
5 determined by using an average current variation per unit time, for example. Further, shorting can be determined by using maximum or minimum current value, or the both.

In the above embodiment, the current sensor is provided between the driving circuit 11 and the anode brush
10 5a through the coupling cable. However, the current sensor 13 can also be provided on the driving circuit 11.

In the above embodiment, the current sensor 13 detects the value of the current supplied to the motor 1 from the power source. However, a shunt resistor is
15 provided at the same position as in the current sensor 13, and the shorting determination can be made by using a voltage between both ends of the shunt resistor.

In the above embodiment, the controller 14 is provided with the temperature correction circuit 14a which
20 corrects the predetermined reference current value supplied from the power source according to a circumferential temperature. However, the controller 14 may not be provided with the temperature correction circuit 14a.

Ins. 26 a
~~In the above embodiment, when the controller 14 determines that the coils 3a 31 have shorted, the controller 14 stops power supply for the motor 1. However, the controller 14 does not need to stop power supply. In~~

Ins.
a7
max.

~~the above embodiment, the warning lamp 15, which informs a user of motor 1 malfunction when coils 3a - 3l are shorting, is provided. However, sounds from a buzzer or the like other than the lamp 15 can be used.~~

5 While the above-described embodiments refer to examples of usage of the present invention, it is understood that the present invention may be applied to other usage, modifications and variations of the same, and is not limited to the disclosure provided herein.